CoinStream® CDS 524 & 726

Continually Exceeding your Expectations of Premium Self Service Coin Destinations

"Premium is defined by performance", not by size, speed or price. Bottom line...Magner's outstanding "Price/Performers" provide you with a product your depositors can really count on, minimize the involvement of your tellers in handling coin transactions, and provide the lowest total cost of ownership over the equipment's useful life.

CoinStream® CDS 524 with optional sign

MAGNER®

Proven Performance and Quality

CoinStream® CDS 524 & 726
Self Service Coin Benefits

Process mixed coin in & mixed coin out into four or six coin bags in sequence. Fewer transaction interruptions for bag changing versus full sort models.

Input Console

- Easy-to-read and understand two (CDS 524) or four-line (CDS 726), by 20 characters per line, backlit LCD display provides customer prompting throughout the entire transaction, with instructions in English and Spanish, plus error status messaging
- User-friendly two-button operation with illuminated Green and Red Buttons
- Automatic coin feeding mechanism ensures optimum feeding of coins and eliminates the need for customers to manually "scrape or push" coins into the machine, reducing chance of customer injury or infection

Coin Counting Section Processes Mixed Coin In and Mixed Coin Out

- Operates at proven optimum throughput speed of 600 coins per minute
- Features highly jam-free operation
- Coins are counted utilizing advanced alloy sensor technology which automatically rejects mutilated coins, foreign coins, and slugs during the counting process, rejected coins are returned to the customer
- Patented automatic debris ejection system removes non-coin material and debris after each customer transaction, routing it to a trash receptacle
- Continuous cleaning mechanism removes sand, pebbles and other small objects
- Counts all six U.S. coin denominations, 1¢, 5¢, 10¢, 25¢, 50¢ and $1 (SBA/Golden), programmable for up to 20 denominations including foreign coins and tokens
- Key lock controls access to counting section, paper roll and coin bagging section
- "Pull-out" shelf design allows easy access to complete counting section for routine service and cleaning
- Acoustical insulation in cabinet plus noise-reducing materials in counting and bagging sections provides the quietest operation available

4 bags of mixed coinCDS 524

Bag Management Section

- Full access to bagging section from the front of the machine for easy bag changeover
- Bag stops are fully programmable, exact and can be set for either pieces or weight
- Coin outlets for mixed coin accommodate direct output to bags, automatic switching fills four (CDS 524) or six (CDS 726) bags sequentially.

6 bags of mixed coinCDS 726

Receipt and Report Output

- High-speed thermal receipt printer uses security paper with special top coating and UV-reactive ink to deter amount alterations and fraudulent receipt duplication
- Easy to read receipt can be customized with name, address, etc., of organization
- Dual service fee percentages are fully programmable
- Grand totals of pieces and value are accumulated by denomination
- Summary report indicates full breakdown of coins processed
- Transaction log recaps all customer transactions

Dimensions and Specifications are approximate and subject to change without notice

Allow 1 1/2" Additional Depth for Sign on CDS 524

Allow 2" additional depth for power cord and DB9 connector on back side of unit or 4 3/8" additional for sign bracket if sign is used on CDS 726.

CoinStream® CDS 524 Optional Additions

Custom Colors
Wraps
Custom Enclosures
Signage and Graphics
Ten-Key Pad
Magnetic Card Reader

RS232 Interface and Host Communication Software

Specifications

Net Weight: 193 lbs.
Sign Weight: 9 lbs.
Power Source: 110/220 VAC
Battery back-up
Temperature Limits: +41° to +104°F
Sound Level: 57 db
Accuracy: 99.995%

Deck: Heavy Duty Stainless Steel
Standard CDS 524 Finish: Black

CoinStream® CDS 726 Optional Additions

Black & Stainless Steel Finish
Custom Colors
Wraps
Custom Enclosures
Signage and Graphics
Ten-Key Pad
Magnetic Card Reader

RS232 Interface and Host Communication Software

Rear Access with Keyboard, Display and Printer

Specifications

Net Weight: 275 lbs.
Sign Weight: 17 lbs.
Power Source: 110/220 VAC
Battery back-up
Temperature Limits: +41° to +104°F
Sound Level: 60 db
Accuracy: 99.995%
Cabinet & Deck: Stainless Steel
Standard CDS 726 Finish: All Stainless

Other Models Available Offering Full 6 Denomination Sort to Bags & Mixed Coin Output to Vaults

LOCAL REPRESENTATIVE:

MAGNER®

Magner Corporation of America, 41 West Street, Middlefield, Connecticut USA 06455
www.selfservicecoin.com Tel: (860) 349-1097 Fax: (860) 349-1257 E-mail: info@magner.com